



HYDAC Technology Corporation

2260 City Line Road,

Bethlehem, PA 18017

TOLL FREE: [877-GO-HYDAC](tel:877-GO-HYDAC) (464-9322)

Website: www.hydac-na.com

Coaxial Valves



1 2 3 4 5

Part Number	Model Description	Thread Size	Nominal Size	Pressure [Max]	Switching Function	Actuator Type	Voltage	Number of Ways
3497463	CX02 -2/2- D/C- 2/10/02 0/012/ 24V	G 1/2	DN10	20 bar 290 psi	Normal y Closed	Electric	24 V	2/2
4026431	CX02 -2/2- D/C- 2/10/02 0/012/ 24V-11	G 1/2	DN10	20 bar 290 psi	Normal y Closed	Electric	24 V	2/2
	CX02 -2/2-							

Part Number	Model Description	Thread Size	Nominal Size	Pressure [Max]	Switching Function	Actuator Type	Voltage	Number of Ways
<u>3667709</u>	D/C- 2/10/02 0/012/ 24V- M12- HW	G 1/2	DN10	20 bar 290 psi	Normal y Closed	Electric	24 V	2/2
<u>4237576</u>	CX02 -2/2- D/C- 2/10/02 0/012/ 24V- M12- Z80	G 1/2	DN10	20 bar 290 psi	Normal y Closed	Electric	24 V	2/2
<u>3438021</u>	CX02 -2/2- D/C- 2/20/02 0/100/ 24V	G 1	DN20	20 bar 290 psi	Normal y Closed	Electric	24 V	2/2
<u>3640099</u>	CX02 -2/2- D/C- 2/20/02 0/100/ 24V- M12	G 1	DN20	20 bar 290 psi	Normal y Closed	Electric	24 V	2/2
<u>3667743</u>	CX02 -2/2- D/C- 2/20/02 0/100/ 24V- M12- HW	G 1	DN20	20 bar 290 psi	Normal y Closed	Electric	24 V	2/2
<u>3642678</u>	CX02 -2/2- D/C- 2/25/02 0/112/23 0V-LED- D	G 1 1/2	DN25	20 bar 290 psi	Normal y Closed	Electric	230 V	2/2

Part Number	Model Description	Thread Size	Nominal Size	Pressure [Max]	Switching Function	Actuator Type	Voltage	Number of Ways
<u>3438024</u>	CX02 -2/2- D/C- 2/25/02 0/114/ 24V	G 1 1/4	DN25	20 bar 290 psi	Normal y Closed	Electric	24 V	2/2
<u>4115669</u>	CX02 -2/2- D/O- 2/32/02 0/112/ 24V	G 1 1/2	DN32	20 bar 290 psi	Normal y Open	Electric	24 V	2/2
<u>3438072</u>	CX03 -2/2- D/C- 2/10/04 0/012/ 24V	G 1/2	DN10	40 bar 580 psi	Normal y Closed	Electric	24 V	2/2
<u>3477823</u>	CX03 -2/2- D/C- 2/10/04 0/012/ 24V- M12	G 1/2	DN10	40 bar 580 psi	Normal y Closed	Electric	24 V	2/2
<u>3438068</u>	CX03 -2/2- D/C- 2/10/04 0/014/ 24V	G 1/4	DN10	40 bar 580 psi	Normal y Closed	Electric	24 V	2/2
<u>4412872</u>	CX03 -2/2- D/C- 2/10/04 0/038- NPT/ 24V	3/8 NPT	DN10	40 bar 580 psi	Normal y Closed	Electric	24 V	2/2
	CX03 -2/2-							

Part Number	Model Description	Thread Size	Nominal Size	Pressure [Max]	Switching Function	Actuator Type	Voltage	Number of Ways
<u>3478120</u>	D/C- 2/15/04 0/034/ 24V- M12	G 3/4	DN15	40 bar 580 psi	Normal y Closed	Electric	24 V	2/2
<u>3549063</u>	CX03 -2/2- D/C- 2/15/04 0/034/ 24VM12 HW DVS	G 3/4	DN15	40 bar 580 psi	Normal y Closed	Electric	24 V	2/2
<u>3438088</u>	CX03 -2/2- D/C- 2/20/04 0/100/ 24V	G 1	DN20	40 bar 580 psi	Normal y Closed	Electric	24 V	2/2
<u>4335136</u>	CX03 -2/2- D/C- 2/20/04 0/100/ 24V-SO	G 1	DN20	40 bar 580 psi	Normal y Closed	Electric	24 V	2/2
<u>3467203</u>	CX03 -2/2- D/C- 2/25/04 0/112/ 24V- M12	G 1 1/2	DN25	40 bar 580 psi	Normal y Closed	Electric	24 V	2/2
<u>3606590</u>	CX03 -2/2- D/C- 2/40/01 6/112/ 24V	G 1 1/2	DN40	N/A	Normal y Closed	Electric	24 V	2/2
	CX03							

Part Number	Model Description	Thread Size	Nominal Size	Pressure [Max]	Switching Function	Actuator Type	Voltage	Number of Ways
<u>3606593</u>	-2/2-D/C-2/50/016/200/24V	G 2	DN50	N/A	Normally Closed	Electric	24 V	2/2
<u>4412873</u>	CX03 -2/2-D/O-2/10/040/038-NPT/24V	3/8 NPT	DN10	40 bar 580 psi	Normally Open	Electric	24 V	2/2
<u>3439088</u>	CX03 -3/2-D/C-2/10/040/012/24V	G 1/2	N/A	40 bar 580 psi	Normally Closed	Electric	24 V	3/2
<u>3486965</u>	CX03 -3/2-D/C-2/10/040/012/24V-HW DMG	G 1/2	N/A	40 bar 580 psi	Normally Closed	Electric	24 V	3/2
<u>4192549</u>	CX03 -3/2-D/C-2/10/040/012/24V-M12-Z80	G 1/2	N/A	40 bar 580 psi	Normally Closed	Electric	24 V	3/2