



HYDAC Technology Corporation

2260 City Line Road,

Bethlehem, PA 18017

TOLL FREE: [877-GO-HYDAC \(464-9322\)](tel:877-GO-HYDAC)

Website: www.hydac-na.com

VM: Medium Pressure Type CD: Electrical Switch

Early warning pressure devices protect the hydraulic circuit from contamination, alerting the operator that the filter element is near capacity and must be changed. The clogging indicator is typically set to trip at 1-bar (14 psid) below the filter bypass setting, to allow the operator sufficient time for element change-out. Available in visual, combo electrical/visual, as well as an extensive list of other options and certifications. A comprehensive offering of clogging indicators ensures that

[+ more](#)



1

Part Number	Model Code Description	Type of Indication	Trip Pressure / Range	Operating Pressure [Max]	Thread	Medium	Maximum Torque
1307257	VM2.5CD.0/-2M0	Electrical Switch	2 bar 29 psi	210 bar 3000 psi	G 1/2	Mineral Oil	24 lb·ft 33 N·m
1294401	VM2.5CD.0/-2M0-OE	Electrical Switch	2 bar 29 psi	210 bar 3000 psi	G 1/2	Mineral Oil	24 lb·ft 33 N·m
1292721	VM2CD.0/-2M0	Electrical Switch	2 bar 29 psi	210 bar 3000 psi	G 1/2	Mineral Oil	24 lb·ft 33 N·m

Part Number	Model Code Description	Type of Indication	Trip Pressure / Range	Operating Pressure [Max]	Thread	Medium	Maximum Torque
<u>1299830</u>	VM2CD.0 /-2M0-OE	Electrical Switch	2 bar 29 psi	210 bar 3000 psi	G 1/2	Mineral Oil	24 lb·ft 33 N·m
<u>1313180</u>	VM3CD.1 /-2M0-30C	Electrical Switch	3 bar 43 psi	210 bar 3000 psi	G 1/2	Mineral Oil	24 lb·ft 33 N·m
<u>1289998</u>	VM5CD.0 /-2M0	Electrical Switch	5 bar 72 psi	210 bar 3000 psi	G 1/2	Mineral Oil	24 lb·ft 33 N·m
<u>1295003</u>	VM5CD.0 /-2M0-OE	Electrical Switch	5 bar 72 psi	210 bar 3000 psi	G 1/2	Mineral Oil	24 lb·ft 33 N·m
<u>1266950</u>	VM5CD.0 /2M20	Electrical Switch	5 bar 72 psi	210 bar 3000 psi	G 1/2	Mineral Oil	24 lb·ft 33 N·m
<u>1289389</u>	VM5CD.0 /-2M20-OE	Electrical Switch	5 bar 72 psi	210 bar 3000 psi	G 1/2	Mineral Oil	24 lb·ft 33 N·m